

GP-3000 SERIES

Industrial AI & Machine Vision Computer





- 01 | GP-3000 Series Introduction
- 02 | Embedded Computer Specification
- 03 | GPU Expansion Box Specification

Dual GPU, Double Power

Industrial AI & Machine Vision Computer



9th/8th

Gen Processor

Powered by 9/8th Generation Intel® Xeon®/Core™ Processor with Intel® C246 Chipset.

Dual


Full-length GPU

Support Maximum Dual 250W Nvidia / AMD GPU Cards
Expansion Up to 328mm in Length

720W

Power Budget

Offer 720W Total System Power Budget for High-end CPU&GPU Computing.



Scalable Design PATENT PENDING

Extremely powerful. And scalable. That's what the GP-3000 series GPU computing system brings to the table. Its crowning achievement is the GPU expansion design. The GP-3000 is the core processing unit, and a selectable GPU Expansion Box (GEB) connects externally and supports up to dual high-end GPU cards. The GP-3000 series is a smart and high-performance GPU computing system.

Multiple Expansion Options

Expansion is one of the primary advantages of the GP-3000. In addition to expanding the number of high-end GPU cards through the GEB, the expansion unit also provides multiple PCIe slots for other applications through high-speed I/O card or frame grabber card, etc. Easily customize the GP-3000 to meet the application needs of different markets.

Upgrade Flexibility

Flexibility for future upgrades is a further advantage. Whether to increase the number of GPU cards or upgrade, there is no need to replace the embedded computer, replace the GEB. This approach dramatically reduces the upgrade cost and retains flexibility for future upgrades.

Configuration Guide

STEP 1


Select an Embedded Computer

**STEP 2**

Select a GPU Expansion Box

**STEP 3**

Configure Your GPU Computer !




Overview

Embedded Computer

**GP-3000 Series**

- High Performance Standalone Computer
- Support Cincoze' Innovative CMI & CFM Module Expansion
- Scalable Design by Adding Versatile GPU Expansion Box

GPU Expansion Box

**GEB Series**

- Offer Various Combination of PCIe Slots for Add-on Cards Expansion
- Support Up to Dual 250W Full-length GPU Cards
- Intelligent Cooling Design for High-end GPU Card Thermal Optimization

Mounting Type

Desktop Mount



- Design for GP-3000 Embedded Computer Only
- With Standard Desktop Mount Bracket

Face-up Mount



- Design for All GP-3000 Series:
 - GP-3000
 - GP-3000/GEB-33 Series
 - GP-3000/GEB-36 Series
- With Standard Wall Mount Bracket

Wall Mount



- Design for All GP-3000 Series:
 - GP-3000
 - GP-3000/GEB-33 Series
 - GP-3000/GEB-36 Series
- With Standard Wall Mount Bracket

19" Rack Mount



- Design for All GP-3000 Series:
 - GP-3000
 - GP-3000/GEB-33 Series
 - GP-3000/GEB-36 Series
- With optional mounting kit:
 - RM01-R10 / RM02-R10 / RM03-R10

GPU Card Dimension Guide



GPU Card Maximum Dimension



System Overview

GP-3000/GEB-33 Series

GP-3000/GEB-36 Series



Power Supply Cabling Guide

GP-3000 supports dual power connectors which are designed for single power source only. Dual power connect must be used at the same time due to 15A current limitation at each power connector.



Item List



1 x Power Cord



1 x Power Supply



2 x Power Cable

Selection Guide

Embedded Computer




Model Name	GP-3000
CPU	9 th /8 th Gen Intel® Xeon®/Core™
Chipset	C246
Memory	2 x SO-DIMM
2.5" Storage	4
Display	1 x VGA , 1 x HDMI , 1 x DP
LAN	5
USB	2 x USB 3.2 Gen2 , 4 x USB 3.2 Gen1
COM	2x RS-232/422/485
Remote Function	1 x Remote Power On/Off , 1 x Remote Reset
Mini PCIe	2
M.2	1 x M.2 Key M Type 2280 , 1 x M.2 Key E Type 2230
Internal USB	1 x USB 2.0
Power Input	9 - 48V
Total Power Budget	220W
Dimension (W x D x H)	105 x 190 x 360 mm
EMC	CE / FCC / ICES-003 / EN50121-3-2 / E-mark
Safety	EN62368-1




GPU Expansion Box



Model Name	GEB-3301	GEB-3601
PCIe x 16	1	2 (PCIe x 8 Lanes)
PCIe x 4	1	1
PCIe x 1	-	1
Internal USB	1 x USB 2.0	1 x USB 2.0
GPU Card Power	2 x 8 Pin Power Connector	4 x 8 Pin Power Connector
Dimension (W x D x H)	104 x 195 x 360 mm	200 x 195 x 360 mm

Configuration Matrix



Model No.	GP-3000	GP-3000/GEB-3301	GP-3000/GEB-3601
GP-3000 	✓	✓	✓
GEB-3301 		✓	
GEB-3601 			✓

Specifications

Weight Information	8 kg	11.2 kg	13.2 kg
Dimension (W x D x H)	105 x 195 x 370 mm	209 x 195 x 370 mm	305 x 195 x 370 mm
Operating Temperature	-40°C to 70°C (Please see page 14 for more information)		
Storage Temperature	40°C to 85°C		
Relative Humidity	95% RH @ 70°C (Non-condensing)		
Mounting	Wall / Desktop / 19" Rack Mount / Stand Mount (Please see page 6 for more information)		
Shock	MIL-STD-810G (pending)		
Vibration	MIL-STD-810G (pending)		
EMC	CE, FCC, ICES-003 Class A, EN50121-3-2 (Railway), E-mark		



- 01 | GP-3000 Series Introduction
- 02 | Embedded Computer Specification
- 03 | GPU Expansion Box Specification

GP-3000

Dual Full-length GPU Expandable Computer



- Supports 9th/8th Gen Intel® Xeon®/Core™ Processor (35W / 65W / 80W)
- 2 x DDR4 SO-DIMM Sockets, Supports ECC/non ECC type up to 2666 MHz, 64GB
- 4 x 2.5" Hot Swappable SATA III HDD/SSD Bays (Max Height 15 mm)
- 1 x M.2 M Key Socket (NVMe), 1 x M.2 E Key Socket (CNVi)
- 2 x Front Accessible SIM Card Slots for Signal Redundancy
- CMI Technology for Various I/O Module Expansions
- CFM Technology for Power Ignition Sensing & PoE Function
- Versatile Mounting Methods (Wall / Stand / Face-up / 19" Rack Mount)
- Military Standard Shock & Vibration Proof (pending)



Overview

GP-3000. A flagship GPU edge computing computer of Cincoze. Its crowning feature is an exclusive GPU Expansion Box that provides expansion for up to two high-end GPU cards and creating a high-performance industrial-grade GPU computing computer.

Extreme Computing Performance

The GP-3000's extreme computing power starts with an 8th or 9th generation Intel® Xeon® or Core™ i3/i5/i7 (Coffee Lake and Coffee Lake-R) CPU, Intel® C246 chipset, and supports two sets of DDR4-2666 ECC/non-ECC SO-DIMM up to 64 GB and can support up to two 250 W high-end GPU cards. With a total power consumption of 720W, it's easy to meet and exceed high-efficiency application requirements. A precision heat dissipation and cooling design quickly wick away heat, keeping the focus squarely on the breathtaking performance of the GP-3000.

Rich Application Functions

The GP-3000 redefines the standard for high-end GPU computers, with high-speed I/O and multiple functions. In addition to the standard five LAN ports and six USB 3.2 ports, the GP-3000 uses Cincoze's exclusive CMI and CFM modular design, which offers expansion modules with eight Gigabit PoE, two USB 3.2, or dual 10 Gb/s LAN ports. Storage options include high-speed M.2 NVMe storage slots and four hot-swappable 2.5" HDD/SSD trays accessible through the front maintenance panel. Together, they meet large-capacity machine vision storage requirements and improve hard disk accessibility for convenient removal and replacement. The IGN module (power ignition sensing) can monitor the on-board battery voltage and set a delayed shutdown time to avoid damage to the system due to unstable current when starting or turning off the engine. This combination of diverse functions provides the flexibility to meet the requirements of different market applications.

Strong and Reliable

In the pursuit of ever-higher standards, the GP-3000 has passed the MIL-STD-810G certification (pending) designed and promulgated by the US Department of Defense to qualify military equipment. The GP-3000 features 9~48 VDC power input, is built for -40 to 70°C temperature operation. The GP-3000 has E-mark and EN50155 (EN50121-3-2 only) certifications, so it is capable of withstanding the rigors of rail and vehicle applications as well as other harsh environments.

Highlights



Cutting-Edge Performance

The GP-3000 is powered by the excellent performance of 8th / 9th generation Intel® Xeon® / Core™ processors. Supports two DDR4 SO-DIMM ECC/Non-ECC memory, up to 64GB. Through the exclusive GPU Expansion Box (GEB) design can flexibly expand up to dual high-end GPU cards. And GP-3000 offers 720W system power budget for high-end GPU Computing applications.



Futureproof Scalability

Upgrades are now easy. In addition to GPU expansion through the GEBs, the GP-3000 also retains flexibility for future upgrades. Whether adding or upgrading GPU cards, the core system remains, and only the GBE is changed. Upgrades become easier, and the expansion possibilities become almost endless.



Mount Anywhere

The GP-3000 supports multiple mounting options for various environment. Mounting options include a wall mount, desktop mount, Face-up mount, and 19" rack mount. Simple.

Specifications

Processor

- 9th Generation Intel Coffee Lake-R S Series CPU:
 - Intel® Xeon® E-2278GE 8 Cores Up to 4.7 GHz, TDP 80W
 - Intel® Xeon® E-2278GEL 8 Cores Up to 3.9 GHz, TDP 35W
 - Intel® Core™ i7-9700E 8 Cores Up to 4.4 GHz, TDP 65W
 - Intel® Core™ i5-9500E 6 Cores Up to 4.2 GHz, TDP 65W
 - Intel® Core™ i3-9100E 4 Cores Up to 3.7 GHz, TDP 65W
 - Intel® Core™ i7-9700TE 8 Cores Up to 3.8 GHz, TDP 35W
 - Intel® Core™ i5-9500TE 6 Cores Up to 3.6 GHz, TDP 35W
 - Intel® Core™ i3-9100TE 4 Cores Up to 3.2 GHz, TDP 35W
- 8th Generation Intel Coffee Lake S Series CPU:
 - Intel® Xeon® E-2176G 6 Cores up to 4.7 GHz, TDP 80W
 - Intel® Xeon® E-2124G 4 Cores up to 4.5 GHz, TDP 71W
 - Intel® Core™ i7-8700 6 Cores up to 4.6 GHz, TDP 65W
 - Intel® Core™ i5-8500 6 Cores, up to 4.1 GHz, TDP 65W
 - Intel® Core™ i3-8100 4 Cores 3.6 GHz, TDP 65W
 - Intel® Core™ i7-8700T 6 Cores up to 4.0 GHz, TDP 35W
 - Intel® Core™ i5-8500T 6 Cores up to 3.5 GHz, TDP 35W
 - Intel® Core™ i3-8100T 4 Cores 3.1 GHz, TDP 35W
 - Intel® Pentium® G5400 2 Cores 3.7 GHz, TDP 58W
 - Intel® Pentium® G5400T 2 Cores 3.1 GHz, TDP 35W
 - Intel® Celeron® G4900 2 Cores 3.1 GHz, TDP 54W
 - Intel® Celeron® G4900T 2 Cores 2.9 GHz, TDP 35W

Chipset

- Intel® C246

Memory

- 2x DDR4-2666/2400 MHz SO-DIMM Sockets
- Supports ECC / non-ECC Type Up to 64 GB
 - * Xeon/i7/i5: Up to DDR4 2666MHz
 - * i3/Pentium/Celeron: Up to DDR4 2400MHz

Graphics

- Integrated Intel® UHD Graphics
 - (Xeon/i7/i5/i3: UHD 630; Pentium/Celeron: UHD 610)
- Supports Triple Independent Display (VGA/DisplayPort/HDMI)

Audio

- Realtek® ALC888, High Definition Audio

BIOS

- AMI BIOS

I/O Interface

- 1x HDMI Connector (4096 x 2160 @30Hz)
- 1x DisplayPort Connector (4096 x 2340 @60Hz)
- 1x VGA Connector (1920 x 1200 @30Hz)
- 5x GbE LAN, RJ45
 - GbE1: Intel® I219-LM
 - GbE2: Intel® I210-IT
 - GbE3: Intel® I210-IT
 - GbE4: Intel® I210-IT
 - GbE5: Intel® I210-IT
- 2x RS-232/422/485 with Auto Flow Control (Supports 5V/12V), DB9
- 2x 10Gbps USB 3.2 Gen2, Type A
- 4x 5Gbps USB 3.2 Gen1, Type A

- 1x Line-out, Phone Jack 3.5mm
- 1x Mic-in, Phone Jack 3.5mm
- 1x ATX Power On/Off Button
- 1x Remote Power On/Off, 2-pin Terminal Block
- 1x Remote Reset, 2-pin Terminal Block
- 1x AT/ATX Mode Switch
- 1x Reset Button
- 1x Clear CMOS Switch

Storage

- 4x 2.5" Front Accessible SATA HDD/SSD Bay (SATA 3.0), Supports Up to 15mm in Height
- 1x M.2 Key M 2280 Socket, Supports PCIe x4 NVMe SSD or SATA SSD (Gen3)
- Supports RAID 0 / 1 / 5 / 10

Expansion

- PCIe
 - Optional GPU Expansion Box
 - 1 x PCIe x 4 + 1 x PCIe x 16
 - 2 x PCIe x 16 (8 Lanes) + 1 x PCIe x 1 + 1 x PCIe x 4
 - * Please See "Chapter 3 – GPU Expansion Box Specification" for more information.
- 2x Full-size Mini-PCIe Socket
- 1x M.2 Key E 2230 Socket, Supports Intel CNVi Module
- 1x M.2 Key M 2280 Socket, Support NVMe/SATA SSD
- 1x Universal Bracket
- 2x SIM Socket
- 7x Antenna Holes

Cincoze Modular Technology

- CMI Interface
 - 1 x High Speed CMI (Combined Multiple I/O) Interface
 - 1 x Low Speed CMI (Combined Multiple I/O) Interface
- CMI Module
 - Optional Modules:
 - 4x GbE LAN, RJ45
 - 4x GbE LAN, M12 A-Coded
 - 2x 10GbE LAN, RJ45
 - 2x RS-232/422/485 with Auto Flow Control (Supports 5V/12V), DB9
 - 16x Optical Isolated DIO(8DI, 8DO), 2x 10 Pin Terminal Block
- CFM Interface
 - 1x CFM(Control Function Module) IGN Interface
 - 1x CFM(Control Function Module) PoE Interface
- CFM Module
 - Optional Module
 - 1x Power Ignition Sensing Module with Delay Time Management and Selectable 12V/24V
 - 1x PoE Function Module Supports Up to 4x PoE+ with Individual port 25.5W
- MEC Module
 - Optional Modules:
 - 2x 5Gbps USB 3.2 Gen1, Type A
 - 2x GbE LAN, RJ45

Other

- 2x Fan Kits (Air-flow isolated from the electronics)
- Support 0.2 sec Instant Reboot Technology
- SuperCap Integrated for CMOS Battery Maintenance-free Operation
- Watchdog Timer: Software Programmable Supports 256 Levels System Reset

Power Requirement

- Supports AT/ATX Power Type
- Power Input Voltage: 9-48 VDC, Single Power Source
- Total Power Budget: 220W
- Connector Type: 2x 3-pin Terminal Block, Each Terminal Block Current Limitation is 15A
- Power Supply:
 - Optional AC/DC or DC/DC 24V 480W Power Supply
 - Optional AC/DC or DC/DC 24V 1000W Power Supply

Physical

- Dimension (WxDxH): 105 x 195 x 370 mm
- Weight: 8 kg
- Extruded Aluminum with Heavy Duty Metal
- Wall Mount / Desktop Mount / 19" Rack Mount / Face-up Mount
- Unibody Chassis
- Jumper-less Design

Protection

- Reverse Power Input Protection
- Over Voltage Protection
 - Protection Range: 51~58V
 - Protection Type: shut down operating voltage, re-power on at the preset level to recover
- Over Current Protection: 30A
- ESD Protection: +/-8kV (air), +/-4kV (contact)
- Surge Protection: 3.84 kV (Impedance 12 ohm 1.2/50us Waveform)

Operating System

- Windows® 10
- Linux: Supports by Project


Environment

- Operating Temperature:


CPU \ GPU	GPU		
	Non-GPU	1 x 250W GPU	2 x 250W GPU
35W	-40°C to 70°C	-40°C to 40°C	-40°C to 35°C
65W	-40°C to 60°C	-40°C to 40°C	-40°C to 35°C
80W	-40°C to 50°C	-40°C to 40°C	-40°C to 35°C

- * With extended temperature peripherals; Ambient with air flow
- * According to IEC60068-2-1, IEC60068-2-2, IEC60068-2-14
- * 100% CPU and GPU without thermal throttling
- Storage Temperature: -40°C to 85°C
- Relative Humidity: 95% RH @ 70°C (Non-condensing)
- Shock: MIL-STD-810G (pending)
- Vibration: MIL-STD-810G (pending)
- EMC: CE, FCC, ICES-003 Class A, EN50121-3-2 (Railway), E-mark
- Safety: LVD (EN62368-1)
- MTBF: 441,283hr

External Layout




Dimensions











Unit: mm

Ordering Information

Available Models



<div><p>GP-3000-R10</p></div>	<p>9th/8th Gen Intel® Xeon®/Core™ GPU Computer, Supports Dual Full-length GPU Expansion Up to 500W</p>
--	--

Package Checklist


	Wall Mount Bracket
	1 x Desktop Mount Kit
	CPU Heatsink and Thermal Pad Kit
	4 x Screw Pack
	1 x Rubber Foot Kit
	2 x Power Terminal Block Connector
	2 x Remote Function Terminal Block Connector
	1 x Utility DVD Driver







Optional Module

GPU Expansion Box




<div><p>GEB-3301-R10</p></div>	GPU Expansion Box with 1x PCIe x16 and 1x PCIe x4 Slots for GP-3000 Series
<div><p>GEB-3601-R10</p></div>	GPU Expansion Box with 2x PCIe x 16 (Signal PCIe x 8), 1x PCIe x 4 and 1 x PCIe x 1 Slots for GP-3000 Series

Accessories - I/O Module






Model No.	Description
<div><p>CMI-LAN01-R12/UB1412</p></div>	CMI Module with 4x Intel I210-IT GbE LAN, RJ45 Port / 1x Universal Bracket with 4x RJ45 Cutout for GP-3000 Series
<div><p>CMI-M12LAN01-R12/UB1410</p></div>	CMI Module with M12 A-Coded Connector, 4x Intel I210-IT GbE LAN / 1x Universal Bracket with 4x M12 Cutout for GP-3000 Series
<div><p>CMI-10GLAN02-R10/UB1428</p></div>	CMI Module with 2x Intel X550 10GbE LAN, RJ45 Port / 1x Universal Bracket with 2x RJ45 Cutout for GP-3000 Series
<div><p>CMI-COM04-R10/UB1403</p></div>	CMI Module with 2x RS232/422/485 Ports (Support 5V/12V) / 1x Universal Bracket with 2x DB9 Cutout for GP-3000 Series
<div><p>CMI-DIO04-R11/UB1418</p></div>	CMI Module with 16DIO (8in 8out) / 1x Universal Bracket with DIO Cutout for GP-3000 Series
<div><p>MEC-USB-M102-15/UB1414</p></div>	Mini-PCle Module with 2x USB 3.0 Ports, 1x 15cm cable / 1x Universal Bracket with 2x USB Cutout for GP-3000 Series






Accessories - Function Module

<div>CFM-PoE07-R10</div> <div></div>	CFM Module with PoE Function, Individual Port 25.5W
<div>CFM-PoE01</div> <div></div>	CFM Module with PoE Function, Individual Port 25.5W
<div>CFM-IGN03-R10</div> <div></div>	CFM Module with Power Ignition Sensing Function, 12V/24V Selectable

Mounting Kit

<div>RM01-R10</div> <div></div>	19" Rack Mount Kit for GP-3000
<div>RM02-R10</div> <div></div>	19" Rack Mount Kit for GP-3000/GEB-33 Series
<div>RM03-R10</div> <div></div>	19" Rack Mount Kit for GP-3000/GEB-36 Series

Power Supply / Power Cord / Power Cable

<div>SDR-480-24</div> <div></div>	DIN Rail Power Supply 480W 24V, SDR-480-24
<div>HEP-1000-24</div> <div></div>	Power Supply 1000W 24V, HEP-1000-24
<div>US Power Cord</div> <div></div>	1.8M US Power Cord, Stripped and Tinned End with Tube
<div>EU Power Cord</div> <div></div>	1.8M EU Power Cord, Stripped and Tinned End with Tube
<div>Power Cable</div> <div></div>	1M Power Cable with 3-Pin Terminal Block Plug, Stripped and Tinned End with Tube




- 01 | GP-3000 Series Introduction
- 02 | Embedded Computer Specification
- 03 | GPU Expansion Box Specification

GEB-3301

GPU Expansion Box with 1 x PCIe x16 and 1 x PCIe x4 Slots for GP-3000 Series




- Support 1 x PCIe x16 Slot for full-length GPU card Expansion
- Support 1 x PCIe x4 Slot for Add-on card Expansion
- Intelligent Cooling Design for High Performance GPU Card
- Military Standard Shock & Vibration Proof (pending)



Specifications

Expansion Slot	<ul style="list-style-type: none">▪ 1 x PCIe x 16 Slot for GPU Card▪ 1 x PCIe x 4 Slot
GPU Card Dimension	<ul style="list-style-type: none">▪ Card Length : 328mm▪ Card Height : 64mm (Standard Triple-Deck)▪ Card Width : 134mm
Internal USB	1 x USB 2.0, Type A
Internal Power Connector	2 x 8-Pin Connector for GPU Card
Total Power Budget	300W
Weight Information	3.2 kg
Dimension (W x D x H)	104 x 195 x 360 mm
MTBF	2,713,254 hr


Dimensions









Unit: mm

Ordering Information


Available Models

<div><p>GEB-3301-R10</p></div>	<p>GPU Expansion Box with 1 x PCIe x 16 and 1 x PCIe x 4 Slots for GP-3000 Series</p>
---	---

Package Checklist



	<p>Wall Mount Bracket</p>
	<p>2 x 8 Pin to 6+2 Pin GPU Power Cable</p>
	<p>2 x Screw Pack</p>
	<p>1 x GPU Card Retainer Screw Pack</p>
	<p>1 x Rubber Foot Kit</p>
	<p>2 x Sponge</p>

GEB-3601



GPU Expansion Box with 2 x PCIe x16 (Signal PCIe x8), 1 x PCIe x4 and 1 x PCIe x1 Slots for GP-3000 Series


- Supports 2 x PCIe x16 Slots for full-length GPU cards Expansion
- Supports 1 x PCIe x4 Slot and 1 x PCIe x1 slot for Add-on cards
- Intelligent Cooling Design for High Performance GPU Card
- Military Standard Shock & Vibration Proof (pending)



Specifications

Expansion Slot	<ul style="list-style-type: none">▪ 2 x PCIe x 16 Slot (PCIe x 8 Signal) for GPU Card▪ 1 x PCIe x 4 Slot▪ 1 x PCIe x 1 Slot
GPU Card Dimension	<ul style="list-style-type: none">▪ Card Length: 328mm▪ Card Height: 64mm (Standard Triple-Deck)▪ Card Width: 134mm
Internal USB	1 x USB2.0, Type A
Internal Power Connector	4 x 8-Pin Connector for GPU Card
Total Power Budget	500W
Weight Information	5.2 kg
Dimension (W x D x H)	200 x 195 x 360 mm
MTBF	1,661,177 hr


Dimensions









Unit: mm

Ordering Information

Available Models

<div><p>GEB-3601-R10</p></div>	<p>GPU Expansion Box with 2 x PCIe x 16 (Signal PCIe x 8), 1 x PCIe x 4 and 1 x PCIe x 1 Slots for GP-3000 Series</p>
---	---

Package Checklist

	<p>Wall Mount Bracket</p>
	<p>4 x 8 Pin to 6+2 Pin GPU Power Cable</p>
	<p>2 x Screw Pack</p>
	<p>1 x GPU Card Retainer Screw Pack</p>
	<p>1 x Rubber Foot Kit</p>
	<p>4 x Sponge</p>